

PROFESSIONAL LCD DISPLAYS PERFECT VISUAL SOLUTIONS



OUR eyeLCD SERIES – DEVELOPED FOR DEMANDING APPLICATIONS





PRESENTATION & INFORMATION



BROADCAST



VR & SIMULATION





VIDEO WALLS



USN Series

(5-mm-Bezel-Class)

XSN Series

(3-mm-Bezel-Class)

ESN Series

(2-mm-Bezel-Class)

STANDALONE



Full-HD Series

(Single LCD Monitors)

4K/Ultra-HD Series

(Single HiRes LCD Monitors

CUSTOM-SOLUTIONS



Broadcast Applications

High Brightness LCD Monitors

24/7 LCD Monitors

Touch Displays

Customized Product Designs

















ALL INFORMATION BUNDLED ON A WALL -

STACKABLE LCD MONITORS

The thin-bezel versions from the eyeLCD series provide all features required for professional video wall installations. Thanks to the minimal gap between the active screen areas of the individual monitors the viewer hardly recognizes disturbing interruptions of the overall displayed content. All images and information can be displayed perfectly organized on a wall. The use of robust components and latest technology ensures best image quality, high resolution and the capability for trouble-free 24/7 continuous operation of the monitors.

Various innovations in display technology enhance the quality of display of the image contents and prevent or minimize the occurrence of negative effects such as "image sticking". Due to their size and their flexible design the monitors can be installed in almost any environment without limitations. Whether video or computer signals - all data formats can be displayed on the screens. In connection with eyevis controllers and software a medium for presentation and information can be achieved that

is ideally suited for control rooms and surveillance centres. But also in multimedia presentations these monitors show their impressive capabilities..

The video wall LCDs provide diverse inputs and outputs, loopthrough functionality for signals and controls as well as internal matrix split controllers which avoids complex cabling on installation. For the devices with OPS standard slot it is possible to $integrate\ an\ eyev is Processing Unit.\ With\ this\ embedded\ controller$ units, it is possible to create a video wall system that can easily be integrated in a network environment. Data and video streams available on the network can be displayed without further controllers or decoding devices.

For a smooth integration of the video wall monitors, eyevis further provides a wide range of professional accessories, such as wall and ceiling mounts, video wall stands, moveable carts and many more.

USN Series

(5-mm-Bezel-Class)

• EYE-LCD-4700-USN-FX-V2 (47")



XSN Series

(3-mm-Bezel-Class)

- EYE-LCD-4600-XSN-FX (46")
- EYE-LCD-5500-XSN-V2 (55")
- EYE-LCD-5500-XSN-LD-FX (55")
- EYE-LCD-5500-XSN-LD-FX-700 (55")

ESN Series

(2-mm-Bezel-Class)

• EYE-LCD-5500-ESN-FX



- Wide product range using the latest LCD technology
- Internal matrix scaler and signal loop-through up to 4K
- · Non-Stick-Mode to avoid burn-in effects
- Stable design

TECHNICAL SPECIFICATIONS								
	Screen Diagonal	Resolution	Brightness	Contrast	Bezel Active-to-Active	Touch Overlay available	OPS Version available	EYE-CAS Colour Adjustmen
EYE-LCD-4600-XSN-FX	46 Inch/116 cm	1920 × 1080 Px	700 cd/m ²	3500:1	3.5 mm	✓		✓
EYE-LCD-4700-USN-FX-V2	47 Inch/119 cm	1920 × 1080 Px	500 cd/m ²	1400 : 1	4.9 mm	✓	✓	✓
EYE-LCD-5500-XSN-V2	55 Inch/139cm	1920 × 1080 Px	700 cd/m ²	4000 : 1	3.5 mm	✓		✓
EYE-LCD-5500-XSN-LD-FX	55 Inch/139cm	1920 × 1080 Px	500 cd/m ²	1400 : 1	3.5 mm	✓	✓	✓
EYE-LCD-5500-XSN-LD-FX-700	55 Inch/139cm	1920 × 1080 Px	700 cd/m ²	1200 : 1	3.5 mm	✓	✓	✓
EYE-LCD-5500-ESN-FX	55 Inch/139cm	1920 × 1080 Px	700 cd/m ²	1200 : 1	<2 mm	✓		✓



Full-HD Series

(Single LCD Monitors)

- EYE-LCD-4600-OPS (46")
- EYE-LCD-4600-LE-700 (46")
- EYE-LCD-5500-OPS (55")
- EYE-LCD-5500-LE-700 (55")
- EYE-LCD-6500-OPS (65")
- EYE-LCD-7000-LE-700 (70")
- EYE-LCD-8000-LE-500/700 (80")

The Advantages at a Glance:

- Different sizes for every field of application
- Versions with OPS-slots and touch-systems available
- Stable design















INDIVIDUALISTS WITH CONVINCING ARGUMENTS -STAND-ALONE FULL-HD LCD MONITORS

Best image quality, high quality components, robust design and long life-time - that's what distinguishes our professional Full-HD LCD monitor solutions from consumer products. The development of the devices in accordance with high industrial standards guarantees that the displays fulfil any demands of sophisticated applications. All products feature professional LCD

technology at the cutting-edge of technology.

A variety of options makes it possible to further optimize and individualize the displays corresponding to the different application areas. These options for example include different touch technologies, monitors with OPS-slots for embedded-PCs, HD-SDI and HDBaseT-Input boards as well as other customerspecific adjustments.

TECHNICAL SPECIFICATIONS								
	Screen Diagonal	Resolution	Brightness	Contrast	Touch Version available	OPS Version available	Customisation available	
EYE-LCD-4600-OPS	46 Inch/116 cm	1920 × 1080 Px	500 cd/m ²	4000 : 1	✓	✓	✓	
EYE-LCD-4600-LE-700	46 Inch/116 cm	1920 × 1080 Px	700 cd/m ²	4000 : 1	✓		✓	
EYE-LCD-5500-OPS	55 Inch/139 cm	1920 × 1080 Px	450 cd/m ²	4000 : 1	✓	✓	✓	
EYE-LCD-5500-LE-700	55 Inch/139 cm	1920 × 1080 Px	700 cd/m ²	4000 : 1	✓		✓	
EYE-LCD-6500-OPS	65 Inch/165 cm	1920 × 1080 Px	360 cd/m ²	4000 : 1		✓		
EYE-LCD-7000-LE-700	70 Inch/177 cm	1920 × 1080 Px	700 cd/m ²	5000:1	✓		✓	
EYE-LCD-8000-LE-500 -700	80 Inch/203 cm	1920 × 1080 Px	500 700 cd/m ²	5000:1	✓		✓	



4K/Ultra-HD Series

(Single HiRes LCD Monitors)

- EYE-LCD-5000-QHD (50")
- EYE-LCD-5800-QHD-V2 (58")
- EYE-LCD-6500-QHD-V2 (65")
- EYE-LCD-8400-QHD-V2 (84")
- EYE-LCD-8500-QHD-LD (85")
- EYE-LCD-9800-QHD-V2 (98")

The Advantages at a Glance:

- Wide product range of the latest LCD technology
- Different sizes for every field of application
- Versions with OPS-slots and touch-systems available
- Applicable for touch tables up to 84-inch
- Stable design















WHEN THE SMALLEST DETAILS COUNT -

HIGH RESOLUTION LCD MONITORS

The pin-sharp Ultra-HD resolution with 3840 × 2160 pixels at 50", 58", 65", 84", 85" or 98" screen diagonal ensures that no image detail gets lost. The high resolution LCD are developed for professional applications under demanding requirements, where they convince through their exceptional image quality. High contrast even in bright light conditions, perfect colour reproduction, a wide viewing angle and sharp images as well as very short reaction times make these monitors the first choice for many areas in which other monitors simply cannot keep up. The 4K/Ultra-HD monitors from the eyeLCD series are ideally suited for application areas that require the display of multiple image signals in native resolution on a single screen, like in security control rooms. But they also provide their outstanding image quality in medical applications, detailed process control, in the media sector and for design, construction or architecture.

TECHNICAL SPECIFICATIONS									
	Screen Diagonal	Resolution	Brightness	Contrast	Signal Inputs	Touch Version available	OPS Version available		
EYE-LCD-5000-QHD	50 inch/127 cm	3840 × 2160 Px	550 cd/m ²	4000:1	4× HDMI 1.4, 1× DP 1.2, 1× VGA	✓	✓		
EYE-LCD-5800-QHD-V2	58 inch/147 cm	3840 × 2160 Px	500 cd/m ²	4500:1	4× HDMI 1.4, 1× DP 1.2, 1× VGA	✓	✓		
EYE-LCD-6500-QHD-V2	65 inch/165 cm	3840 × 2160 Px	450 cd/m ²	4000:1	4× HDMI 1.4, 1× DP 1.2, 1× VGA	✓			
EYE-LCD-8400-QHD-V2	84 inch/213 cm	3840 × 2160 Px	500 cd/m ²	1400 : 1	4× HDMI 1.4, 1× DP 1.2	✓	✓		
EYE-LCD-8500-QHD-LD	85 inch/215 cm	3840 × 2160 Px	500 cd/m ²	3000:1	4× HDMI 1.4, 1× DP 1.2, 1× VGA	✓	✓		
EYE-LCD-9800-QHD-V2	98 inch/248 cm	3840 × 2160 Px	500 cd/m ²	1300 : 1	4× HDMI 1.4, 1× DP 1.2, 1× VGA	✓	✓		

Studio Monitors

(Optimised for low temperature operation)

EYE-LCD-5500-XSN-V2-BC (55")

Preview Monitors

(Portable LCD Monitors)

EYE-LCD-1700-HB-BC-V2 (17")

















PARTNERS FOR SUCCESSFUL PRODUCTIONS -

CUSTOMISED SOLUTIONS FOR BROADCASTERS

For the special requirements in broadcast areas eyevis offers customized solutions. The portable preview monitors from the HB-BC series provide all the necessary connections and timings for the broadcast sector. The anti-glare screen and high brightness allow excellent image quality even under difficult lighting conditions. The rugged protective housing and the 12-Volt operation mode make these devices the ideal preview monitor even in outdoor productions.

For installations in studio environments with a special requirement for the display of certain colour temperatures eyevis provides a broadcast version of the seamless LCD monitors from the XSN-BC series. Due to a special treatment of the LCD panel, the BC version is particularly suitable for the use in TV studios. For all LCD models with OPS slot, it is possible to use it for the integration of a broadcast standard (3G)SDI signal input.

TECHNICAL SPECIFICATIONS BROADCAST MONITORS						
	Screen Diagonal	Resolution	Brightness	Contrast	Special Feature	
EYE-LCD-1700-HB-BC-V2	17.1 inch/43,8 cm	1920 × 1080 Px	1300 cd/m ²	500 : 1	Preview monitor for broadcast applications	
EYE-LCD-5500-XSN-V2-BC	55 inch/139 cm	1920 × 1080 Px	700 cd/m ²	4000:1	Video wall LCD from the 3-mm- Bezel-Class, optimized for colour temperatures from 2800K to 6500K	

SIMPLY TOUCH -

TOUCH SYSTEMS FOR eyeLCD DISPLAYS



Direct interaction with digital content is now part of everyday life. For our displays from the eyeLCD series, we meet this requirement with a touch option that is available for almost all types of displays. For the single monitors this touch system is integrated directly into the display housing and can be ordered with different protective glass types and up to 50 simultaneous touch points.



A MATTER OF TASTE

CUSTOMISED SPECIAL SOLUTIONS

Our competences include:

- Sourcing of high-quality components
- Construction of customized housings, if necessary with special protection or air conditioning technologies
- Installation of different touch technologies
- Integration of embedded PC systems or additional input facilities
- Development of specific base frames and brackets for the installation of completed products



Example Double-Display:

- Double-sided Digital Signage Display with high brightness panel and standard LCD panel
- Completely new product design including component selection, housing design, integration of a network-based player





Numerous projects require a display solution that is not available "off the shelf". eyevis is constantly seeking to fulfil the individual ideas and wishes of its customers.

After an initial feasibility study, you can count on our long-lasting experience in the development and production of digital display solutions, an own research centre and manufacturing. In a constant dialogue with or clients we will finally present a solution that perfectly meets the customers' requirements.

eyevis' customers benefit from latest technology and competent employees with great experience in development and construction.

Displays can also be suited to the individual corporate design and they are available in all RAL-colours.

eyevis addresses each individual customer request and offers ideal solutions through a wide and professional product range.





INCREDIBLY BRIGHT HIGH BRIGHTNESS LCD MONITORS





HIGHEST RELIABILITY LCD MONITORS FOR 24/7 OPERATION



The ideal display solutions for perfect image representation even in the harshest conditions. With a brightness of up to 5000 nit, these displays provide best image quality in areas where normal displays push their limits. For example, these displays are ideal for installations behind shop windows – even in direct sunlight.

The LCD monitors type EYE-LCD-4200-24LE in 42" and EYE-LCD-4700-24LE in 47" were especially developed for the toughest operating conditions. Various protective mechanisms prevent burn-in effects with permanently displayed static content – under warranty. Their slim design makes them an ideal solution for control rooms or signage applications.

TECHNICAL SPECIFICATIONS 24/7-DISPLAYS / HIGH BRIGHTNESS LCD MONITORS Resolution Screen diagonal Brightness Contrast Special feature EYE-LCD-4200-24LE 1300 : 1 42 inch/106 cm 1920 × 1080 Px 700 cd/m² Optimized for 24/7 operation Optimized for 24/7 operation FYF-I CD-4700-24I F 47 inch/119 cm 1920 × 1080 Px 700 cd/m² 1300:1 High brightness LCD FYF-I CD-4600-XHB 55 inch/116 cm 1920 × 1080 Px 5000 cd/m² 4000 · 1 for signage applications



AUTOMATIC COLOR ADJUSTMENT EYE-LCD-CAS





HIGH PERFORMANCE PROCESSING OPS-MODULE



The Color-Adjustment-System is the ideal tool for setting the color of LCD displays from the eyeLCD series. The system includes hardware and software components for the measuring and alignment procedure of LCD video walls. The color adjustment works fully automatically which makes the procedure very simple and time-efficient.

To facilitate the installation, control and signal connectivity of video walls and LCD displays, eyevis has developed a new series of intelligent OPS-LCD displays. Through an OPS conform eyevisProcessingUnit the electronics for signal processing is directly integrated into the displays. The OPS-slot further offers the possibility of integrating additional input options such as HD-Base-T or 3G-SDI.

FOR A PERFECT FINISH -

STANDS, BRACKETS AND STACKING FRAMES

- Wall brackets in various versions (fixed, tiltable, etc.)
- Motorized adjustable lift systems, partially tiltable for (touch) table applications
- Special video wall mounts with front service support for simple service and screen replacement
- Special wall mounts for video walls
- Stands in various designs
- Stacking frames for video walls, e.g. for flexible use in trade show and event construction
- Moveable video wall carts for 2×2 or 3×3 displays
- Expandable video wall stand systems
- Design and installation of project-specific solutions



AT A GLANCE

THE ADVANTAGES OF THE EYEVIS eyeLCD SERIES



OUTSTANDING QUALITY

For the displays of our eyeLCD series, we use only industrial components to ensure the highest quality and reliability.



4K/ULTRA HD

Already since 2007 displays of this resolution belong to our portfolio. This allows you to benefit from our years of experience in the manufacturing, installation and control of these displays.



SERVICE & SUPPORT

Various service and maintenance contracts as well as the shipping of original spare parts are key elements of our service concept.



LED BACKLIGHT

All devices in the eyeLCD series use LED backlight technology. As Edge LED or Direct LED this provides homogeneous brightness, low power consumption and slim design.



24/7-CONTINUOUS OPERATION

High-quality components and innovative features allow the operation of our displays in 24/7 continuous operation under certain operating conditions



OUTSTANDING BRIGHTNESS

The high brightness of our displays ensures that the contents are always readable and recognizable even in difficult lighting conditions.



THINNEST BEZELS

In our wide range of video wall displays, you will always find products with the currently thinnest frame so that the appearance of your pictures is almost seamless.



TOUCH OPTION

For all products from the eyeLCD series a touch system is optionally available that enables the precise and robust interaction with the represented content.



COLOR ADJUSTMENT SYSTEM

With the EYE-LCD-CAS system we offer a unique solution for the semi-automated matching of color and brightness of our video wall displays.



EYEVISPROCESSINGUNIT

The devices with OPS slot offer the possibility to install an eyevisProcessingUnit (OPS standard module) that provides even more intelligence and networking capabilities of the display.



IP PROTECTION CLASS

Thanks to their robust design our displays are ready for demanding application in tougher environments. Some devices even offer IP-rated protection.



FULL HD

All our displays support at least the current HD standard of 1920×1080 pixels.



The high quality of our products is backed up by the outstanding quality of our service technicians and the support we offer to our customers. Apart from regular repairs in-house or on-site, the supply of original spare parts and maintenance works on demand, we offer a range of service level agreements that ensure highest availability of your system.

Our experience shows that preventive maintenance and active support return the investment by leading to optimal system availability, the productivity of the system is guaranteed and operating costs can be reduced. Regular maintenance is a prerequisite for stable, trouble-free operation of your eyevis system. Therefore eyevis offers maintenance contracts that are tailored to the needs of your installation.

Updated information on our projects and products with many photos as well as the possibility of communicating with other interested customers can also be found at:

- twitter.com/eyevis
- www.facebook.com/eyevis
- www.linkedin.com/companies/eyevis



Scan the QR code and visit our website to find more detailed information on all of our products and services, download brochures and data sheets, or watch the product videos.

) eyevis GmbH

Hundsschleestrasse 23 72766 Reutlingen Germany

Tel.: +49 (0) 71 21 - 4 33 03-0 Fax: +49 (0) 71 21 - 4 33 03-22

> Web: www.eyevis.com E-Mail: info@eyevis.de